

RECOMMENDED FALL PROTECTION EQUIPMENT

If the **equipment** you need is not listed on our website please feel free to call us at our toll free number, **1.800.480.3521**, for **Fall Protection equipment** pricing and availability.

SPECIAL HARNESS

Center Large Front D-ring minimum 2 ¼" ID; Side D-ring and Back D-ring also require minimum 2 ¼" ID.

Specify Size - X-SMALL, SMALL, MEDIUM, LARGE, X-LARGE, XX-LARGE, and XXX-LARGE



BEAM STRAP

D-1003006 Anchorage Connector, Tie-off Adaptor, pass thru type x 6 ft.

D-1003000 Anchorage Connector, Tie-off Adaptor, pass thru type x 3 ft.



LANYARDS

6FT. TIE BACK LANYARD

D-1241206 EZ-Stop II, Tie-Back Lanyard, 1" polyester web w/ 100% Tie-Off, floating D-ring on each leg end.



M-050066/6FTAF Lanyard, 6 ft. 2 Leg Web Lanyard w/ 2 Adjustable D-rings, 3 Carabiners & S.A. Pack.



WORK POSITIONING LANYARD

D-1231380 Web Rebar Assembly, self locking snap hooks each end w/ 9502058 aluminum hook (2 ¼" gate opening) at center x 18".



D-1231382 Web Rebar Assembly, self locking snap hooks each end w/ 2000114 (2 - 3/16" gate opening) Carabiner x 18".



ROPE GRAB

D-1224005 Rope Adjuster/ 3 ft. S/A lanyard and 2004339 hook, Manual
D-5000335 Rope Grab, 5/8" Diameter, Auto



SCAFFOLD CHOKER

D-1201391 Scaffold choker w/ D-ring x 24 in.



SHOCK ABSORBING LANYARD

D-1244415 Shockwave 2, Double-leg Lanyard, 100 % Tie-Off w/ Large Carabiners.



SELF-RETRACTING LIFELINE (SRL)

D-3102100 Tie-Back Talon Self-Retracting Lifeline, Twin-Leg 7.5 ft. web, Delta Comfort Pad, 2 lanyard keepers, and tie-back hook ends (3/4" gate opening)



TOWER RESCUE KIT

Complete Tower Rescue Kit includes:

Double Micro Pulleys, (1) Top & (1) Bottom, (1) 20' X 3/8" Rope, (3) Carabiners, (1) 100' X 7/16" Rope, (1) Adj. Rigging Sling, (1) Rope Bag (1) Antron Descender, (1) 3/8" Thimble, (1) 24" Rope Guard, (2) Rope Labels, (2) Rope Log Books

Optional Rope Lengths: 100 ft., 200 ft., 300 ft., 400 ft., 500 ft., 600 ft.



C-MICROD Micro Hauler Top



C-RP110D Double Micro Rescue, w/ becket



R-5999246- Rope Thimble, 3/8"



R-6010097 Anthron Descender, 7/16"



R-2354120N Petzl ID Descender/Belay, goes up to 1/2" (general use)



R-6124241 24" Rope Guard (black)



R-756106 Adjustable Rigging Sling, 2 - 6 ft. (yellow)



Triple Action Carabiner

FP-9005G-TPK-50 D-shaped Carabiner, Triple Action-50kN with 3,600 lbs. (3 Stage Auto Locking Gate) Gate & Captive Eye pin, 1.25" Opening



Double Action Carabiner

FP-9005G-PHS D-shaped Carabiner, Double Action-50kN with 3,600 lbs. Gate & Captive Eye pin, 1.25" Opening.



FIRST- MAN-UP SYSTEM

D-2104530- First-Man-Up System 6-12 ft. adjustable pole, tie-off adaptor tool, hook tool, 1003000 3 ft. tie-off adaptor, carrying bag & video. 2104527 Original Hook Tool & 3,600 lbs. Gated Hook Tool.

D-2104531- First-Man-Up System 8-16 ft. adjustable pole, tie-off adaptor tool, hook tool, 1003000 3 ft. tie-off adaptor, carrying bag & video. 2104527 Original Hook Tool & 3,600 lbs. Gated Hook Tool.



RESCUE POSITIONING DEVICE (RPD)

D-3602000 w/ 4:1 Ratio, slings, hooks, and storage bag w/ specified length of travel
Specify Length Needed



RESCUE POLE

Y-1117 Rescue Clip w/ 18 ft. Extension Pole & Carabiner, Pole will go as small as 4 ft.
Great for Traveling on Helicopters.



Bag 24x12x12, SAFETY CONNECTION, INC. LOGO DUFFEL BAG



LAD-SAF FIXED LADDER SAFETY SYSTEM

D-6116280 Lad-Saf Standard Top Bracket Assembly



D-6140XXX 3/8" Stainless Steel Aircraft Cable
Specify Length



D-6110400 Cable Guide-must be installed every 25 ft.



D-6116540 Cable Sleeve for Lad-Saf System, w/ attached 2000112 carabiner (for use with 8mm or 9.5 mm (3/8") dia. 1x7 or 7x19 solid core cable).



D-6100090 Galvanized Bottom Bracket for Lad-Saf Cable System. Hardware included.



HORIZONTAL LIFELINE SYSTEMS

M-X000XX Xenon HLL system, Engineered Fall Protection system to accommodate multiple workers at one time. Kits include Xenon 4-in-1 shock absorber, intermediate bracket, two stainless steel D-bolt anchorage connectors, swageless fast-attach fitting, anchor shackle, thimble, cable clips, hardware and instruction manual.
Specify Length



D-7602020 Cable HLL Specify length Sayflite system 3/8" cable, cable grip, turnbuckle and Zorbit energy absorber (systems over 60 ft. includes 2 Zorbit energy absorbers).



D-7600502 Synthetic Rope HLL Specify length Sayflin system kernmantle rope, tensioner, 2 tie-off adaptors and storage bag.



ANCHORAGE CONNECTORS

D-2104700 Glyder 2 sliding beam anchor fits 3-1/2" to 14" wide flange up to 1-1/4" thick.



D-2110941 Glyder sliding beam anchor fits 6" to 18" wide flange up to 2-1/2" thick



D-2108406 Fixed beam anchor, fits up to 1-1/2" thick x 2-1/2" - 12" wide specify thickness of beam flange.



SELF-CLOSING LADDER SAFETY GATES

P-LSG-(SIZE)-(GAL; PCY; SST; ALU) Self-closing swing gate that meets all OSHA/ANSI dimensional requirements and standards. They can be installed onto railings that are up to 2" round or square tubing. Additional adaptor kits for mounting are available for railings that are greater than 2" outside diameter tubing or angle iron. They are available in Powder Coat Yellow, Hot dipped Galvanized, Stainless Steel, and Aluminum; allowing them to be installed in all working environments and conditions. Please refer to the chart below for available sizes and opening ranges to fit your needs.

MODEL	OPENING
LSG-15-(GAL;PCY;SST;ALU)	13 ³ / ₄ " - 17 ¹ / ₂ "
LSG-18-(GAL;PCY;SST;ALU)	16 ³ / ₄ " - 20 ¹ / ₂ "
LSG-21-(GAL;PCY;SST;ALU)	19 ³ / ₄ " - 23 ¹ / ₂ "
LSG-24-(GAL;PCY;SST;ALU)	22 ³ / ₄ " - 26 ¹ / ₂ "
LSG-27-(GAL;PCY;SST;ALU)	25 ³ / ₄ " - 29 ¹ / ₂ "
LSG-30-(GAL;PCY;SST;ALU)	28 ³ / ₄ " - 32 ¹ / ₂ "
LSG-33-(GAL;PCY;SST;ALU)	31 ³ / ₄ " - 35 ¹ / ₂ "
LSG-36-(GAL;PCY;SST;ALU)	34 ³ / ₄ " - 38 ¹ / ₂ "
LSG-40-(GAL;PCY;SST;ALU)	38 ³ / ₄ " - 42 ¹ / ₂ "
LSG-44-(GAL;PCY;SST;ALU)	42 ³ / ₄ " - 46 ¹ / ₂ "
LSG-48-(GAL;PCY;SST;ALU)	46 ³ / ₄ " - 50 ¹ / ₂ "



You can install the self-closing ladder safety gates yourself or call us so we can do the installation for you using our professional installers. Please call 1.800.480.3521 for a Sales Quote.